

Louvers

EXTERIOR

SEAMLESS DESIGNER uPVC PLANKS



10 Years
warranty

WIDER WIDTH

FASTER INSTALLATION

EUROPEAN TECHNOLOGY



As pioneers in the industry, we at Euro Pratik intend to produce and provide innovative high-end lifestyle products with the use of cutting edge new technologies. We aspire to serve a range of demands that sprout from various market and lifestyle trends that emerge all across the world.

We take pride in our young and dynamic team that works tirelessly, dedicated to R&D and delivering products up to date. We at Euro Pratik intend to never stop expanding and adding to our 16+ years of experience.

We surge ahead with an aim to bring about a revolutionary shift in the concept of living spaces, by creating world class interior and exterior vision. Delivering to a colossal amount of 150+ cities across India, Nepal, Sri Lanka, and Bangladesh, at Euro Pratik we like to keep an edge with the ever evolving trends and needs of the market. We cater to every price point to make sure our customers are never out of options. Hence, over the years we have created our niche in the lifestyle segment and have emerged as a pioneer in the lifestyle industry whilst holding a wide range of products to choose from.

EXTERIOR Louvers

SEAMLESS DESIGNER uPVC PLANKS



Non
Warping



Fire
Resistant



Scratch
Resistant



Quick
Installation



Durability
& Strength



Environment
Friendly



Water
Proof



Borer
Proof



Termite
Proof





UPVC03A 2750mm x 185mm



UPVC03B 2750mm x 185mm

FACADES & CEILINGS





UPVC03C 2750mm x 185mm



UPVC03D 2750mm x 185mm

FACADES & CEILINGS





UPVC05A 2750mm x 185mm



UPVC05B 2750mm x 185mm

FACADES & CEILINGS



UPVC05C 2750mm x 185mm




UPVC05D 2750mm x 185mm

FACADES & CEILINGS






UPVC05E 2750mm x 185mm



UPVC01A 2750mm x 100mm

FACADES & CEILINGS





UPVC01B 2750mm x 100mm



UPVC01C 2750mm x 100mm

FACADES & CEILINGS





UPVC07A 2750mm x 185mm



UPVC07B 2750mm x 185mm

FACADES & CEILINGS



UPVC07C 2750mm x 185mm



UPVC07D 2750mm x 185mm

FACADES & CEILINGS

The reinforced structural design ensures exceptional strength and stability. Its robust construction provides stringent and non warping properties, maintaining its shape and integrity over time even under extreme conditions.

The top - UV stabilised film offers a luxurious and natural looking wood finish, providing an eco-friendly solution, without harming the mother natures natural resources ensuring an elegant aesthetic.

Crafted with advanced European technology, EXTERIOR LOUVERS provide the highest durability and a premium finish, making them a top choice for both interior & exterior applications.

L PROFILES FOR EDGES & CORNERS
AVAILABLE IN ALL COLOURS
2750mm x 50mm x 50mm

why Exterior Louvers?

Among the various materials available, uPVC stands out as a popular choice due to its durability, affordability, and resistance to weathering.

Adding more, uPVC is Inherently Fire Retardant, Slow to Ignite, Self Extinguishing and has a Limited Flame Spread. The key lies in the composition of uPVC, which contains additives that enhance its fire retardant properties.

Being unplasticized it does not emit toxic gas when subjected to high temperature.

uPVC can be recycled and repurposed into new article, once it has reached the end of its useful life.

In addition the energy efficiency of uPVC assists in reducing Carbon emissions and energy bills, making it a sustainable option.

INSTALLATION GUIDE

SURFACE PREPARATION

Uneven Surface: Fix aluminum channel or joists at the area where the panels are to be applied, ensuring they are placed at regular intervals.(not more than 375mm)

Even Surface: If the surface is even, you can fix the panels directly without additional preparation.

PANEL PLACEMENT

Place the first EXTERIOR LOUVERS panel at the starting point. Attach a clip to the underside of the first EXTERIOR LOUVERS panel. Fix the clip using a drywall Screw. Need be apply silicone on the base for better bonding. Each panel should have 8 clips attached at regular intervals for secure installation.

INSTALLING SUBSEQUENT PANELS

Place the second panel next to the first panel. Ensure the sides of the panels interlock in a tongue-and-groove manner, similar to how charcoal louvers interlock. Attach a clip to the underside of the second EXTERIOR LOUVERS panels and fix it using a drywall screw, following the same method as for the first panel.

EXTERIOR Louvers

SEAMLESS DESIGNER uPVC PLANKS

EURO PRATIK®
An Opus of Products

✉ info@europratik.com | follow us on
🌐 www.europratik.com | 